



ImageIR® 9500

High-end Thermography Camera

INFRA^TEC.

Europe's leading specialist for infrared sensors and measurement technology



- 1) ImageIR® 9500 with interchangeable lenses from InfraTec
- 2) Thermographic software IRBIS® 3
- 3) Microscopic thermography with (1,280 × 720) IR pixels

- Cooled FPA photon detector with (1,280 × 720) IR pixels
- Opto-mechanical MicroScan with (2,560 × 1,440) IR pixels
- Full-frame rate up to 120 Hz, GigE Vision compatible
- Up to 1.5 kHz with (320 × 180) IR pixels
- Snapshot detector, integrated trigger interface
- Extremely short integration times in the microsecond range
- Thermal resolution better than 0.025 K
- Made in Germany



www.InfraTec.eu

www.InfraTec-infrared.com

NEW



Spectral range	(3.5 ... 4.8) μm
Pitch	12 μm
Detector	MCT
Detector format (IR pixels)	(1,280 \times 720)
Image format with opto-mechanical MicroScan (IR pixels)	(2,560 \times 1,440)
Image acquisition	Snapshot
Readout mode	ITR / IWR
Aperture ratio	f/2.0
Detector cooling	Stirling cooler
Temperature measuring range	(-20 ... 1,200) $^{\circ}\text{C}$, up to 2,000 $^{\circ}\text{C}^*$
Measurement accuracy	± 1 $^{\circ}\text{C}$ or ± 1 %
Temperature resolution @ 30 $^{\circ}\text{C}$	Better than 0.025 K
Frame rate (full / half / quarter / sub frame)*	Up to 120 Hz / 446 Hz / 1,517 Hz / 16,053 Hz
Window mode	Yes
Focus	Manually, motorised or automatically*
Dynamic range	14 bit
Integration time	(1 ... 20,000) μs
Rotating aperture wheel and filter wheel*	Up to 5 positions
Interfaces	10 GigE, GigE*, 2 \times CAMLink*, HDMI*
Trigger	3 IN / 2 OUT, TTL
Analogue signals*, IRIG B*	2 IN / 2 OUT, yes
Tripod adapter	1/4" and 3/8" photo thread, 2 \times M5
Power supply	24 V DC, wide-range power supply (100 ... 240) V AC
Storage and operation temperature	(-40 ... 70) $^{\circ}\text{C}$, (-20 ... 50) $^{\circ}\text{C}$
Protection degree	IP54, IEC 60529
Dimensions; weight	(241 \times 123 \times 160) mm; 4.7 kg (without lens)
Analysis and evaluation software	IRBIS [®] 3, IRBIS [®] 3 view, IRBIS [®] 3 plus*, IRBIS [®] 3 professional*, IRBIS [®] 3 control*, IRBIS [®] 3 online*, IRBIS [®] 3 process*, IRBIS [®] 3 active*, IRBIS [®] 3 mosaic*, IRBIS [®] 3 vision*

* Depending on model

In regard to InfraTec's wide range of products, the ImageIR[®] 9500 thermographic camera offers an alternative especially for the international market. Its highly sensitive **cooled focal plane array photon detector** is based on mercury cadmium telluride (MCT) and provides **(1,280 \times 720) IR pixels**. The geometrical resolution can even be increased to (2,560 \times 1,440) IR pixels with the MicroScan function. Due to its **outstanding thermal sensitivity up to 0.025 K**, users can create low-noise, fine-resolution images using the quadruplication of the image formats. In addition, this model of the high-end ImageIR[®] camera series impresses with **extremely short integration times in the microsecond range**, very high frame rates of 120 Hz, which increase to 1,500 Hz in sub-frame with (320 \times 180) IR pixels.

The ImageIR[®] 9500 is suitable for highly demanding applications in science and industry, object monitoring and microthermographic analysis of extremely small structures. It is equipped with an integrated 10 GigE interface that enables data exchange between camera and computer at a speed of 10 Gbps. Due to the **modular concept consisting of optics, detector and interface modules**, the camera can be individually configured and optimally adapted to the respective task. The same purpose is served by the **range of high-quality, radiometric precision optics**, which ranges from telephoto lenses, standard and wide-angle lenses to macro- and microscopic lenses.

Lenses	Focal length (mm)	FOV ($^{\circ}$)	IFOV (mrad)
Standard lens	25	(34.2 \times 19.6)	0.48
Telephoto lens	50	(17.5 \times 9.9)	0.24
Telephoto lens	100	(8.8 \times 4.9)	0.12
Supertelephoto lens	200	(4.4 \times 2.5)	0.06

Macro and microscopic lenses	Object distance (mm)	Object size (mm)	Pixel size (μm)
Close-up for telephoto lens 50 mm	300	(92 \times 52)	72
Close-up for telephoto lens 100 mm	500	(77 \times 43)	60
Microscopic lens M=1.0 \times	40	(15 \times 9)	12
Microscopic lens M=8.0 \times	14	(1.9 \times 1.1)	1.5

Headquarters

InfraTec GmbH
Infrarotsensorik und Messtechnik
 Gostritzer Str. 61 – 63
 01217 Dresden / GERMANY
 Phone +49 351 871-8630
 Fax +49 351 871-8727
 E-mail thermo@InfraTec.de

USA office

InfraTec infrared LLC
 5048 Tennyson Pkwy.
 Plano TX 75024 / USA
 Phone +1 844-226-3722 (toll free)
 E-mail thermo@InfraTec-infrared.com